

## FIGURES

The first digits in the figure number are the same as the related paragraph number. The digits after the hyphen are the number within the paragraph. Most figures are located at the end of the related paragraph.

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
AC 29.45-1	H-V Requirements	B-21
AC 29.45-2	IGE Controllability Requirements	B-22
AC 29.45-3	Shaft Horsepower vs. Turbine Outlet Temperature - Sea Level Standard Day	B-23
AC 29.45-4	Uninstalled Takeoff Power Available	B-24
AC 29.45-5	Installed Takeoff Power Available, Anti-Ice Off, 400 RPM	B-25
AC 29.45-6	Power Assurance Check Chart	B-26
AC 29.53-1	Takeoff Performance Category A	B-33
AC 29.53A-1	Takeoff Performance Category A	B-35
AC 29.59-1	Category A Vertical Takeoff Profile Ground Level Heliport	B-44
AC 29.59-2	Category A Vertical Takeoff Profile Pinnacle	B-45
AC 29.59A-1	Category A Vertical Takeoff Profile Ground Level Heliport	B-54
AC 29.59A-2	Category A Vertical Takeoff Profile Elevated Heliport	B-55
AC 29.63-1	Conventional Takeoff Profile Category B	B-58
AC 29.71-1	Autorotational Characteristics - Typical	B-67
AC 29.75-1	Category A Conventional Landing - Clear Heliport	B-77

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
AC 29.75-2	Category A Vertical Landing	B-78
AC 29.75A-1	Category A Conventional Landing - Clear Heliport	B-87
AC 29.75A-2	Category A Vertical Landing	B-88
AC 29.79-1	Height-Velocity Diagram	B-96
AC 29.79-2	Altitude/Weight Accountability	B-97
AC 29.175-1	Static Longitudinal Stability	B-113
AC 29.251-1	Demonstration Points	B-125
AC 29.337-1	Load Factor Gross Weight Curve	C-7
AC 29.351-1	Sample Yaw/Forward Speed Diagram	C-12
AC 29.351-2	Sample Yaw/Forward Speed Diagram	C-14
AC 29.427-1	(View Looking Forward)	C-28
AC 29.427-2	(View Looking Forward)	C-29
AC 29.571-1	Comparison Percent of Time in Level Flight	C-56
AC 29.621-1	Example of Casting Load Sheet Retract Actuator Support-Landing Gear	D-23
AC 29.621-2	Castings to be Static Tested for Model XYZ	D-25
AC 29.773-1	Cockpit Visibility	D-72
AC 29.801-1	Sea State Code - World Meteorological Organization	D-94
AC 29.863-1	Flammable Fluids Fire Protection Flow Chart	D-126
AC 29.865-1	Summary of Part 133 Rotorcraft Load Combinations Certifiable Under § 29.865	D-134
AC 29.877-1	Continuous Icing-Temperature vs. Altitude Limits	D-155

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
AC 29.877-2	Intermittent Icing-Temperature vs. Altitude Limits	D-156
AC 29.877-3	Mean Effective Drop Diameter-Microns	D-157
AC 29.877-4	Intermittent Icing-Liquid Water Content vs. Drop Diameter	D-158
AC 29.877-5	Supercooled Clouds	D-159
AC 29.903C-1	Estimated Path of Fragments	E-23
AC 29.903C -2	Single One-Third Disc Fragment	E-24
AC 29.903C -3	Intermediate and Small Pieces of Debris	E-25
AC 29.903C -4	Blade Fragment Definition	E-26
AC 29.903C -5	Distribution of Translational and Rotational Kinetic Energy of Rotor-Component Fragments as a Function of Fragment Size $\Theta$	E-27
AC 29.903C -6	Cross Section through Aircraft at Plane of Rotation of the Engine Disk Fragment	E-28
AC 29.923A-1	Rotor Drive System Endurance	E-48
AC 29.923A-2	Takeoff Run Portion of Rotor Drive System Endurance Test If 2 ½ Minute OEI Rating is Requested.	E-49
AC 29.923A-3	Takeoff Run Portion of Rotor Drive System Endurance Test If 30 Second/2 Minute OEI Rating is Requested.	E-50
AC 29.931-1	Cantilevered Shaft, First Critical Speed	E-62
AC 29.931-2	Shaft Between Support Bearings, First Critical Speed	E-62
AC 29.952-1	Static Tension and Shear Loading Modes	E-87
AC 29.952-2	Hose Assembly Tests	E-88

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
AC 29.952-3	Minimum Average and Individual Loads for Hose and Hose-End Fitting Combinations	E-89
AC 29.952-4	Typical Method of Breakaway Fuel Fitting Load Calculations	E-90
AC 29.952-5	Typical Methods of Frangible or Deformable Attachment Load Calculations (Frangible Bolts)	E-91
AC 29.952-6	Typical Methods of Frangible or Deformable Attachment Load Calculations (Frangible Baffle)	E-92
AC 29.955A-1	Fuel Flow	E-102
AC 29.1041-1	Additional Cooling Test Point	E-139
AC 29.1045-1	All-Engine-Critical Altitude Additional Cooling Test Point	E-146
AC 29.1191-1	Table of Materials and Gages Acceptable for Fireproof Protective Devices with Flat Surface Geometries	E-190
AC 29.1329-1	Deviation Profile	F-46
AC 29.1329-2	Operational Limitation	F-48
AC 29.1419-1	Continuous Icing-Temperature vs. Altitude Limits	F-92
AC 29.1419-2	Intermittent Icing-Temperature vs. Altitude Limits	F-93
AC 29.1419-3	Continuous Icing-Liquid Water Content vs Drop Diameter	F-94
AC 29.1419-4	Intermittent Icing-Liquid Water Content vs. Drop Diameter	F-95
AC 29.MG 3-1	Category II Approach Evaluation	MG 3-5
AC 29.MG 3-2	Category II Approach Evaluation (cont.)	MG 3-6

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
AC 29.MG 5-1	Acceptable Ultimate Load Factor for Agricultural Dispensing Equipment Design	MG 5-2
AC 29.MG 5-2	Sketch of Tank Pressure Test	MG 5-5
AC 29.MG 6-1	Typical Liquid Oxygen System	MG 6-17
AC 29.MG 6-2	Typical Liquid Oxygen System - Using Combination Valve	MG 6-18
AC 29 MG 9-1	Installed Engine Fuel Flow Capacity Check	MG 9-8
AC 29 MG 11-1	S-N or P-N Curve Usage	MG 11-14
AC 29 MG 11-2	Crack Growth for Single Element Structure	MG 11-17
AC 29 MG 11-3	Crack Growth for Remaining Elements of Multiple Element Structure	MG 11-19
AC 29 MG 12-1	U.S. Operational (Part 133) Rotorcraft-Load Combination Versus Applicable Cargo Type Data and Definition Summary	MG 12-9
AC 29 MG 12-2	Sequential Simulation of Hook Dynamic Roll-Out	MG 12-24
AC 29 MG 12-3	Rescue Devices Chart	MG 12-35
AC 29 MG 12-4	Summary of Relevant Information for U.S. Part 133 Rotorcraft Load Combinations Under § 29.865	MG 12-40
AC 29.APX B-1	Rotorcraft Dynamic Stability Requirements for IFR	Apdx B-20